

ZKP8007

Thermal Receipt Printer



ZKP8007 is a cost-effective thermal receipt printer. It supports NVLOGO picture downloading and BMP format printing. This thermal receipt printer can be desk-top or wall mounted. This thermal receipt printer offers simple paper refill, and it is widely used in POS system, the retail industry, the food courts, the beverage industry, etc.

Features

- Supports NVLOGO picture downloading and printing (BMP format)
- Compatible with ESC/POS print instruction set
- Compact and simple paper refill
- Cost-effective
- Wall-mounted and desk-top mode

Applications



Fashion Chain Stores



Supermarkets



Food Courts

Specifications

Print Method	Direct thermal
Paper Width	79.5±0.5mm
Print Speed	180 mm/s
Print Width	72mm
Character Set	Alphanumeric; International
Character Size	ANK Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots)
Print Resolution	576 dots/line or 512 dots/line (Adjusted by command)
Line Spacing	3.75mm (Adjusted by command)
Column Number	Font A: 42 columns or 48 columns
Extension Character Sheet	PC437(Std.Europe)/(Katakana)/PC850(Multilingual) /PC860(Portugal)/PC863(Canadian)/ PC865(Nordic)/(West Europe)/(Greek)/(Hebrew)/(East Europe)/(Iran)/(WPC1252)/ PC866(Cyrillic#2)/PC852(Latin2)/(PC858)/(IranII)/(Latvian)/(Arabic)/(PT1511251)
Barcode Types	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODABAR / ITF / CODE39 / CODE93 / CODE128
Auto Cutter	Partial
Interfaces	USB, USB+LAN
Print Command	ESC/POS
Power Adapter	Input: AC 100-240V/50-60 Hz; Output: DC24V/2.5A
Printer Input	DC 24V/2.5A
Cash Drawer	DC 24V/1A
Cutter Life	1.5 million cuts
Printer Head Life	150KM
Dimensions (D*W*H)	189*145*140 (mm)
Net Weight	1.00 Kg
Weight with Packaging	1.85 Kg
Operating Temperature	0°C to 45°C
Storage Temperature	-10°C to 60°C
Operating Humidity	10% to 80%RH
Storage Humidity	10% to 90%RH
Certificates	CE; FCC; RoHS

