

ZK15 Series

All in One Biometric Smart POS Terminal



Features

- Power-efficient Intel® Celeron J1900 2.0 GHz Quad-Core processor
- Optional Intel® Core i3 and i5 processor
- 15" Bezel-Free true-flat display with PCAP touch
- Multiple I/O interfaces for peripherals
- Standard with 2G RAM and 32G SSD
- Standard with 8C high-definition digital tube
- Optional 3 tracks MSR, attached VFD&12.1" customer display
- Faster installation and maintainability

Optional



Magnetic Stripe
Card Reader



2nd LCD Display Screen



Barcode Scanner



Mifare/RFID



Thermal Printer



Cash Drawer



VFD Customer Display



Fingerprint

Specifications

System	
Processor	Intel® Celeron J1900 Quad-Core processor (2.0 GHz)
System Memory	2GB Standard, DDR3L 1333MHz (Max.8GB)
Storage Device	32GB Msata SSD Standard, 1*2.5" HDD / 2.5" SSD
OS Supported	Windows 7, Windows 8, Windows 10 IoT Enterprise, POS Ready 7, Linux
Audio	Realtek ALC662
Display and Touch	
Type	15" TFT LCD, LED Backlight
Resolution	1024×768
Touch Screen	Five-Wire Analog Resistive or Projected Capacitive
Customer Display	LED(8C digital tube)
External I/O Ports	
VGA	1*DB-15
USB	5*USB2.0, 1*USB3.0
Serial	1*RS232(Max.4pcs)
LAN	1*RJ45
Audio	1*Line-out
Power	
Power Supply	Adaptor 12V DC 5A
Physical Environmental	
Operating Temperature	0 °C ~ 35 °C at 20%-80% Humidity
Storage Temperature	- 20 °C ~ 55 °C at 20%-80% Humidity
Dimensions(W×H×D)	358*368*222mm
Packing Dimensions	405*430*260mm
Net Weight	5.5kg
Packing Weight	6.5kg
Certification	CE FCC
Color	Black
Options & Peripherals	
Second Display	12.1" TFT LCD
Customer Display(VFD)	VFD(2*20 lines)
MSR	3 Tracks
Fingerprint	USB fingerprint reader(SLK20R)



ZKTECO CO.,LTD.
www.zkteco.com
E-mail: sales@zkteco.com

© Copyright 2018. ZKTECO CO.,LTD. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

